



DCA CONSTRUCTION PRODUCTS

SEAL/EXPAND-Tite Water-Based Adhesive/Surface Primer

Applications:

For use on concrete, plastic and metal surfaces, SEAL/EXPAND-Tite Primer is used to bond SEAL-Tite or EXPAND-Tite Waterstops to various substrates prior to concrete placement. Recommended for use on vertical installations and horizontal installations when necessary.

| Description | SEAL/EXPAND-Tite Primer |
|-------------------------------|--|
| % Solids: | 33% min. |
| Solvent Type: | Water |
| Flash Point | 200° min. |
| Weight/Gallon: | 8.0 lbs. |
| Dry Time @ 77°F (25°C): | 10 Minutes |
| Dry Time @ 40°F (4°C): | 60 Minutes |
| Clean Up: | Soap and Water |
| Coverage Per Gallon: | Approx. 400 sq. ft. on wet cast concrete. Less on dry cast concrete. |
| Appropriate Substrates: | Concrete, Plastic, Metal |
| Min. Storage Temperature: | 40°F (4°C): Product should not be allowed to freeze. |
| Min. Application Temperature: | 40°F (4°C) |
| Surface When Dry: | Tacky |

American Made  Veteran Owned

Waterstop • Forming Accessories • Rebar Supports • Mesh Supports • Prestressed Accessories

DCA CONSTRUCTION PRODUCTS, LLC

10421 Industrial Drive • Garrettsville, OH 44231 • (888) 833-8308 (Toll-Free) or (330) 527-4308 • Fax: (330) 527-2440